


RiseAtlas625T™ with SmartPark-function

SystemRoMedic™



Special version with SmartPark-function – for users weighing up to 285 kg/625 lbs

- SWL 285 kg/625 lbs
- Transfer motor for powered transfer in rail
- Special version for use in rail systems with end point charging
- Modern, elegant and hygienic design
- Unusually small measurements and extremely low weight
- For all rail systems, in all settings and in all types of rooms
- Large lifting area and possibility of both very low and very high lifting
- In all situations and for all user needs
- Very easy to use, providing safe working conditions and allowing the caregiver to remain close to the user throughout the entire lifting procedure
- Moves silently and gently, soft start and stop
- Ergonomic and easy-to-use hand control
- On/Off-button on the hand control prevents unauthorized use of lift functions
- Manual emergency stop
- Electrical and manual emergency lowering
- Overload protection
- Over speed protection
- Slack strap switch
- Night light
- Efficient strap control preventing accidental twisting of the lift strap
- High capacity, environmentally friendly NiMH battery
- Unique charging solution, with one trolley for two charging options (in-rail/end point charging)
- RiseAtlas625T, with SmartPark-function is, as standard, preset to function with end point charging
- Discreet information panel
- Easy to service
- Diagnostics, a special software available as an accessory allows a PC to access further information about the ceiling lift unit
- Many accessories for safe, easy and individually adapted lifting of users in most transfer situations

RiseAtlas625T™ with SmartPark-function

For professional and highly functional care environments with a harmonic and human atmosphere.



Ergonomic and user-friendly hand control

PRODUCT SPECIFICATION

Item No. **Product**
50100053 ___ RiseAtlas625T, with SmartPark-function

RiseAtlas625T, with SmartPark-function is supplied with hand control and charger. Sling bar ordered separately.

ACCESSORIES

Item No.	Product	Description
70200047	___ 9V battery and cable	For emergency lowering
70200048	___ Software for diagnostics	Software
50400066	___ Cover to charger	For all models and special versions of RiseAtlas
50400048	___ Parking Placard	For convenient storing of sling bars, manuals and lifting slings
50400332	___ Parking Placard BariBar	For convenient storing of BariBar and lifting slings
70200071	___ SlingBar XS	250 mm / 9.8"
70200001	___ SlingBar S	350 mm / 13.8"
70200002	___ SlingBar M	450 mm / 17.7"
70200003	___ SlingBar L	600 mm / 23.6"
70200042	___ SlingBarSpreader M	Side bars for SlingBar XS/S/M/L
70200072	___ BariBar	Four-point sling bar for ceiling lift units, SWL 454 kg/1000 lbs
70200017	___ Sling bar RFL X4	Four-point sling crossbar, SWL 300 kg/660 lbs
70200053-		
70200058	___ Lift strap extension	Extension straps, 6 lengths: 370-970 mm/ 14.6"-38.2"

TECHNICAL INFORMATION

Safe working load: _____ 285 kg / 625 lbs
 Material, chassis: _____ Aluminium
 Material, cover: _____ Non flammable ABS plastic
 Measurements, length x width x height: ___266 x 151 x 156 mm / 10.5 x 5.9 x 6.1"
 Weight: _____ 7.5 kg / 16.5 lbs
 Transfer in rail: _____ Transfer motor
 Transfer speed, without load: _____ 140 mm / 5.5" per sec
 Transfer speed, with load: _____ 120 mm / 4.7" per sec
 Hand control: _____ Electrical, 6 buttons
 Lifting range: _____ 2400 cm / 94.5"
 Lifting speed, without load: _____ 50 mm / 2.0" per sec
 Lifting speed, with load: _____ 39 mm / 1.5" per sec
 Sound level, with load: _____ 55 dB(A)
 Efficient strap control: _____ Standard
 Emergency lowering: _____ Electrical and manual
 Emergency stop: _____ Manual
 Night light: _____ Standard
 Battery: _____ NIMH 24V 3.2 Ah/768Wh
 Hand control charging: _____ No
 In-rail charging: _____ No
 End point charging: _____ Standard
 Protection class, lift unit: _____ IP20
 Protection class, hand control: _____ IPX4



CE RiseAtlas625T, with SmartPark-function meets the requirements of the Medical Devices Directive for Class 1 products 93/42/EEC.

Please visit www.handicare.com for more information.



Handicare AB
 Maskinvägen 17,
 SE 972 54 Luleå, SWEDEN
 Tel: 08-557 62 200
 Fax: 08-557 62 299
www.handicare.com
info@handicare.se

SystemRoMedic™ is a complete solution for easy transfers. The concept encompasses four product areas that meet most needs in different transfer situations.

Transfer, between two locations. **Positioning**, within the same location.

Support, for mobility. **Lifting**, both manual and mechanical.