

RiseAtlas450MTM with QuickTrolleySystem, high humidity

SystemRoMedicTM



QuickTrolleySystem facilitates mounting and dismantling from the rail and provides the possibility to move the ceiling lift unit between different rail systems in different rooms for increased utilization and cost efficiency.



With QuickTrolleySystem, the ceiling lift unit and the lift strap can easily be preset to an angle of 45 or 90 degrees towards the rail for smooth and convenient transfers of patients from one room to another.

Special version for wet environments – for patients weighing up to 205 kg/450 lbs

- SWL 205 kg/450 lbs
- Manual transfer in rail
- Special version for use in environments where moisture and dampness are present
- Modern, elegant and hygienic design
- Unusually small measurements and extremely low weight
- For all rail systems, in all settings and in all types of rooms
- Large lifting area and possibility of both very low and very high lifting
- In all situations and for all patient needs
- Handicare's unique SystemRoMedicTM QuickTrolleySystem provides more flexibility, versatility and convenience
- Very easy to use, providing safe working conditions and allowing the caregiver to remain close to the patient throughout the entire lifting procedure
- Moves silently and gently, soft start and stop
- Ergonomic and easy-to-use hand control
- On/Off-button on the hand control prevents unauthorized use of lift functions
- Manual emergency stop
- Electrical and manual emergency lowering
- Overload protection
- Over speed protection
- Slack strap switch
- Night light
- Efficient strap control preventing accidental twisting of the lift strap
- High capacity, environmentally friendly NiMH battery
- Unique charging solution, with one trolley for two charging options (in-rail/end point charging)
- Discreet information panel
- Easy to service
- Diagnostics, a special software available as an accessory allows a PC to access further information about the ceiling lift unit
- Many accessories for safe, easy and individually adapted lifting of patients in most transfer situations



RiseAtlas450M™ with QuickTrolleySystem, high humidity

For professional and highly functional care environments with a harmonic and human atmosphere.



Ergonomic and user-friendly hand control



PRODUCT SPECIFICATION

Item No. Product

50100051 ___ RiseAtlas450M, with QuickTrolleySystem, high humidity

RiseAtlas450M, with QuickTrolleySystem, high humidity is supplied with hand control and charger. Sling bar ordered separately.

ACCESSORIES

Item No.	Product	Description
70200046	QuickTrolley450	Quick release trolley
70200051	QuickTrolley450 70 mm	Quick release trolley, lowering lift unit by 70 mm / 2.76"
70200075	QuickTrolleyUniversal 360	Quick release trolley, turns 360 degrees
70200048	Software for diagnostics	Software
50400066	Cover to charger	For all models and special versions of RiseAtlas
50400048	Parking Placard	For convenient storing of sling bars, manuals and lifting slings
50400332	Parking Placard BariBar	For convenient storing of BariBar and lifting slings
70200071	SlingBar XS	250 mm / 9.8"
70200001	SlingBar S	350 mm / 13.8"
70200002	SlingBar M	450 mm / 17.7"
70200003	SlingBar L	600 mm / 23.6"
70200042	SlingBarSpreader M	Side bars for SlingBar XS/S/M/L
70200072	BariBar	Four-point sling bar for ceiling lift units, SWL 454 kg/1000 lbs
70200017	Sling bar RFL X4	Four-point sling crossbar, SWL 300 kg/660 lbs
70200053-		
70200058	Lift strap extension	Extension straps, 6 lengths: 370-970 mm / 14.6"-38.2"

TECHNICAL INFORMATION

Safe working load: _____ 205 kg / 450 lbs
Material, chassis: _____ Aluminium
Material, cover: _____ Non flammable ABS plastic
Measurements, length x width x height: _____ 266 x 151 x 156 mm / 10.5 x 5.9 x 6.1"
Weight: _____ 7.3 kg / 16.1 lbs
Transfer in rail: _____ Manual
Hand control: _____ Electrical, 4 buttons
Lifting range: _____ 2400 mm / 70.8"
Lifting speed, without load: _____ 50 mm / 2.0" per sec
Lifting speed, with load: _____ 39 mm / 1.5" per sec
Sound level, with load: _____ 55 dB(A)
Efficient strap control: _____ Standard
Emergency lowering: _____ Electrical and manual
Emergency stop: _____ Manual
Night light: _____ Standard
Battery: _____ NiMH 24V 3.2 Ah/768Wh
Hand control charging: _____ No
In-rail charging: _____ Optional, standard
End point charging: _____ Optional, standard
Protection class, lift unit: _____ IPX4
Protection class, hand control: _____ IPX4



RiseAtlas450M with QuickTrolleySystem, high humidity meets the requirements of the Medical Devices Directive for Class 1 products 93/42/EEC.

Please visit www.handicare.com/us for more information.



handicare

Handicare
2201 Hangar Place, Suite 200
Allentown, PA 18109
Tel: 610 266 5260 • Fax: 610 266 5266
Toll Free: 866 276 LIFT/5438
www.handicare.com/us • customerservice.usa@handicare.com

SystemFoMedic™ is a complete solution for easy transfers. The concept encompasses four product areas that meet most needs in different transfer situations.

Transfer, between two locations. **Positioning**, within the same location.

Support, for mobility. **Lifting**, both manual and mechanical.